

Lampade alogene, tensione di rete, attacco singolo




Aree applicative


- Lavoro cinematografico e televisivo professionale

Caratteristiche prodotto


- Funzionamento con tensione di rete 120 V | 230 V | 240 V
- Temperatura di colore: 2.900 K | 3.000 K (con durata maggiore)
- Temperatura di colore: 3.200 K (per lavoro cinematografico e televisivo professionale)
- Temperatura di colore: 3.400 K (per la massima efficienza luminosa)




Scheda della famiglia di prodotto



358722_Halogen Lamp 64662



341357_HALOGEN STUDIO LAMP 64670



488277_HALOGEN LAMP 93591, 93592

Scheda della famiglia di prodotto

Dati tecnici

Descrizione del prodotto	Informazio ni sul prodotto	Dati elettrici	Dati fotometri ci	Dimensioni e peso		
	Numero d'ordine	Tensione nominale	Temperat ura di colore	Diametro	Lunghezza	Area illuminata
64501 150 W 120 V	64501 150W 120V	120 V	3250 K	120 mm	550 mm	11,0*2,2 mm ²
64502 150 W 230 V	64502 150W GX6.	230 V	3200 K	180 mm	550 mm	13,0*1,9 mm ²
64502 150 W 240 V	64502 150W 240V	240 V	3200 K	1800 mm	550 mm	13,0*1,9 mm ²
64504 150 W 230 V	64504 A1/248 15	230 V	3200 K	1800 mm	620 mm	9,6*12,5 mm ²
64505 200 W 230 V ¹⁾	64505 200W GX6.	230 V	3200 K	185 mm	530 mm	9,6*12,5 mm ²
64505 200 W 230 V ¹⁾	64505 200W 240V	240 V	3200 K	185 mm	530 mm	9,5*12,5 mm ²
64512 300 W 120 V ¹⁾	64512 300W GX6.	120 V	3350 K	185 mm	530 mm	10,0*12,5 mm ²
64514 300 W 120 V ¹⁾	64514 300W GX6.	120 V	3200 K	185 mm	530 mm	10,0*12,5 mm ²
64515 300 W 230 V ¹⁾	64515 300W 230V	230 V	3300 K	185 mm	530 mm	9,8*12,5 mm ²
64515 300 W 240 V ¹⁾	64515 300W GX6.	240 V	3350 K	185 mm	530 mm	10,0*12,5 mm ²
64516 300 W 230 V ¹⁾	64516 300W GX6.	230 V	3150 K	185 mm	530 mm	9,8*12,5 mm ²
64516 300 W 240 V ¹⁾	64516 300W GX6.	240 V	3150 K	185 mm	530 mm	9,7*12,5 mm ²
64540 650 W 230 V	64540 BVM 650W	230 V	3400 K	240 mm	575 mm	14,0*15,0 mm ²
64540 650 W 240 V	64540 BVM 650W	240 V	3400 K	240 mm	575 mm	14,0*15,0 mm ²
64575 1000 W 230 V	64575 1000W 230	230 V	3400 K	240 mm	675 mm	14,0*14,0 mm ²
64575 1000 W 240 V	64575 1000W GX6	240 V	3400 K	240 mm	675 mm	14,0*14,0 mm ²
64748XS 1000W 240V	64748 XS 1000W	240 V	3200 K	2220 mm	950 mm	
64748XS 1000W 230V	64748 XS 1000W	230 V	3200 K	2220 mm	950 mm	
64662 300 W 230 V ²⁾	64662 300W GY9.	230 V	2900 K	150 mm	800 mm	9,0*11,0 mm ²
64672 500 W 230 V	64672 M40 500W	230 V	2900 K	220 mm	899 mm	12,0*11,0 mm ²
64672 500 W 240 V	64672 M40 500W	240 V	2900 K	220 mm	899 mm	12,0*11,0 mm ²

Scheda della famiglia di prodotto

	Informazio ni sul prodotto	Dati elettrici	Dati fotometri ci	Dimensioni e peso		
Descrizione del prodotto	Numero d'ordine	Tensione nominale	Temperat ura di colore	Diametro	Lunghezza	Area illuminata
64686 650 W 230 V	64686 DYR 650W	230 V	3200 K	210 mm	640 mm	10,0*10,0 mm ^{2 2)}
64686 650 W 240 V	64686 DYR 650W	240 V	3200 K	210 mm	640 mm	10,0*10,0 mm ^{2 2)}
93592 400 W 230 V ³⁾	93592 400W 230V	230 V	3200 K	200 mm	770 mm	10,7*12,2 mm ²
64662 300 W 240 V	64662 M38 300W	240 V	2900 K	1750 mm	800 mm	9,0*11,0 mm ²
64540 650 W 230 V	64540 650W GX6.	230 V	3400 K	2200 mm	575 mm	
64686 650 W 230 V	64686 650W GY9.	230 V	3200 K	2100 mm	640 mm	
64540 650 W 240 V	64540 650W GX6.	240 V	3400 K	2200 mm	575 mm	
64686 650 W 240 V	64686 650W 240V	240 V	3200 K	2100 mm	640 mm	

		Durata	Dati di prodotto aggiuntivi	Caratteristiche	
Descrizione del prodotto	Diametro del filamento	Durata	Attacco (denominazi one da norma)	Posizione di funzionamento	Dimmerabile
64501 150 W 120 V	2,2 mm	50 h	GX6.35	h90	
64502 150 W 230 V	1,9 mm	50 h	GX6.35	Universale	
64502 150 W 240 V		50 h	GX6.35	Universale	
64504 150 W 230 V		25 h	G6.35	s 90	
64505 200 W 230 V ¹⁾	12,5 mm	25 h	GX6.35	s 90	
64505 200 W 230 V ¹⁾	12,5 mm	25 h	GX6.35	s 90	
64512 300 W 120 V ¹⁾	12,5 mm	15 h	GX6.35	s 90	
64514 300 W 120 V ¹⁾	12,5 mm	75 h	GX6.35	Other	
64515 300 W 230 V ¹⁾	12,5 mm	15 h	GX6.35	s 90	
64515 300 W 240 V ¹⁾	12,5 mm	15 h	GX6.35	s 90	
64516 300 W 230 V ¹⁾	12,5 mm	75 h	GX6.35	s 90	
64516 300 W 240 V ¹⁾	12,5 mm	75 h	GX6.35	s 90	
64540 650 W 230 V	15,0 mm	15 h	GX6.35	Universale	Sì
64540 650 W 240 V	15,0 mm	15 h	GX6.35	Universale	
64575 1000 W 230 V	14,0 mm	15 h	GX6.35	s	
64575 1000 W 240 V	14,0 mm	15 h	GX6.35	s	
64748XS 1000W 240V			GY9.5	S180	
64748XS 1000W 230V			GY9.5	S180	
64662 300 W 230 V ²⁾	11,0 mm	2000 h	GY9.5	Universale	
64672 500 W 230 V	11,0 mm	2000 h	GY9.5	Universale	

Scheda della famiglia di prodotto

		Durata	Dati di prodotto aggiuntivi	Caratteristiche	
Descrizione del prodotto	Diametro del filamento	Durata	Attacco (denominazione da norma)	Posizione di funzionamento	Dimmerabile
64672 500 W 240 V	11,0 mm	2000 h	GY9.5	Universale	
64686 650 W 230 V	10,0 mm	50 h	GY9.5	Universale	
64686 650 W 240 V	10,0 mm	50 h	GY9.5	Universale	
93592 400 W 230 V ³⁾	12,2 mm	75 h	GY9.5	s 90	
64662 300 W 240 V	11,0 mm	2000 h	GY9.5	Universale	
64540 650 W 230 V			GX6.35	Other	
64686 650 W 230 V			GY9.5	Universale	
64540 650 W 240 V			GX6.35	Other	
64686 650 W 240 V			GY9.5	Other	

		Classificazioni specifiche del paese		Dati logistici	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Descrizione del prodotto	Codice ANSI	Codice LIF		EAN 10 of contained light source	Date of Declaration
64501 150 W 120 V	Other			4008321746030	25-04-2024
64502 150 W 230 V	Other			4052899080751	25-04-2024
64502 150 W 240 V	Other			4052899363236	25-04-2024
64504 150 W 230 V	Other	A1/249		4052899101654	06-03-2024
64505 200 W 230 V ¹⁾	Other			4008321746078	25-04-2024
64505 200 W 230 V ¹⁾	Other			4008321746092	25-04-2024
64512 300 W 120 V ¹⁾	Other			4008321746115	25-04-2024
64514 300 W 120 V ¹⁾	Other	CP/96		4008321746139	25-04-2024
64515 300 W 230 V ¹⁾	Other			4008321746153	25-04-2024
64515 300 W 240 V ¹⁾	Other			4008321746177	25-04-2024
64516 300 W 230 V ¹⁾	Other	CP/97		4008321746191	25-04-2024
64516 300 W 240 V ¹⁾	Other	CP/97		4008321746214	25-04-2024
64540 650 W 230 V	BVM			4052899158221	25-04-2024
64540 650 W 240 V	BVM			4052899158245	25-04-2024
64575 1000 W 230 V	EGY			4052899274556	25-04-2024
64575 1000 W 240 V	EGY			4052899274570	25-04-2024
64748XS 1000W 240V				4052899545380	22-04-2024
64748XS 1000W 230V				4052899545366	22-04-2024
64662 300 W 230 V ²⁾	Other			4052899015449	22-04-2024
64672 500 W 230 V	Other			4008321098559	22-04-2024
64672 500 W 240 V	Other			4008321098535	22-04-2024
64686 650 W 230 V	Other			4052899158269	05-03-2024
64686 650 W 240 V	Other			4052899158283	05-03-2024
93592 400 W 230 V ³⁾	Other			4050300481531	05-03-2024

Scheda della famiglia di prodotto

	Classificazioni specifiche del paese		Dati logistici	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Descrizione del prodotto	Codice ANSI	Codice LIF	EAN 10 of contained light source	Date of Declaration
64662 300 W 240 V	Other	M/38	4052899144248	22-04-2024
64540 650 W 230 V	Other			06-03-2024
64686 650 W 230 V	Other			06-03-2024
64540 650 W 240 V	Other			06-03-2024
64686 650 W 240 V	Other			06-03-2024

Descrizione del prodotto	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
64501 150 W 120 V	4050300279237 4008321746030	No declarable substances contained	In work
64502 150 W 230 V	4008321133335 4008321746054 4052899080751	No declarable substances contained	No declarable substances contained
64502 150 W 240 V	4052899080775 4052899363236	No declarable substances contained	In work
64504 150 W 230 V	4052899101654	No declarable substances contained	No declarable substances contained
64505 200 W 230 V ¹⁾	4008321098436 4008321173881 4008321746078	No declarable substances contained	No declarable substances contained
64505 200 W 230 V ¹⁾	4008321098610 4008321746092	No declarable substances contained	No declarable substances contained
64512 300 W 120 V ¹⁾	4008321098634 4008321746115	No declarable substances contained	No declarable substances contained
64514 300 W 120 V ¹⁾	4008321098672 4008321746139	No declarable substances contained	No declarable substances contained
64515 300 W 230 V ¹⁾	4008321098696 4008321746153	No declarable substances contained	No declarable substances contained
64515 300 W 240 V ¹⁾	4008321189110 4008321746177	No declarable substances contained	No declarable substances contained
64516 300 W 230 V ¹⁾	4008321098733 4008321746191	No declarable substances contained	No declarable substances contained
64516 300 W 240 V ¹⁾	4008321098757 4008321746214	No declarable substances contained	No declarable substances contained
64540 650 W 230 V	4052899158221	No declarable substances contained	No declarable substances contained
64540 650 W 240 V	4052899158245	No declarable substances contained	No declarable substances contained
64575 1000 W 230 V	4008321098856 4052899274556	No declarable substances contained	No declarable substances contained
64575 1000 W 240 V	4008321087775 4008321098450 4052899274570	No declarable substances contained	No declarable substances contained

Scheda della famiglia di prodotto

Descrizione del prodotto	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
64748XS 1000W 240V	4052899545380	No declarable substances contained	No declarable substances contained
64748XS 1000W 230V	4052899545366	No declarable substances contained	No declarable substances contained
64662 300 W 230 V ²⁾	4008321097873 4052899015449	No declarable substances contained	No declarable substances contained
64672 500 W 230 V	4008321098559	No declarable substances contained	No declarable substances contained
64672 500 W 240 V	4008321098535	No declarable substances contained	No declarable substances contained
64686 650 W 230 V	4052899158269	No declarable substances contained	No declarable substances contained
64686 650 W 240 V	4052899158283	No declarable substances contained	No declarable substances contained
93592 400 W 230 V ³⁾	4050300481531	No declarable substances contained	No declarable substances contained
64662 300 W 240 V	4052899144248	No declarable substances contained	No declarable substances contained
64540 650 W 230 V	4008321098818		In work
64686 650 W 230 V	4008321098498 4008321133359		In work
64540 650 W 240 V	4008321098795		In work
64686 650 W 240 V	4008321098511		In work

1) Con tecnologia di pinzatura al quarzo
2) With monoplane filament
3) Disponibile su richiesta

Scheda della famiglia di prodotto

Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

Referenze/links

Per maggiori informazioni sulla tecnologia pinch, puoi consultare la brochure:

“A whole lotta shakin’ goin’ on!” Nuove lampade alogene con tecnologia pinch del bulbo in quarzo. (122 W 100 DE 08/05)

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.