

LINEARlight FLEX Protect ADVANCED

Moduli LED per applicazioni professionali e industriali



Caratteristiche prodotto

- Striscia LED flessibile e tagliabile
- Classe di protezione: IP67
- Fine White (3,5 SDCM)
- Resistente alla nebbia salina

Vantaggi prodotto

- Molto lungo per file luminose continue
- Ampia libertà di progettazione grazie ai moduli flessibili e separabili
- Silicone ad alte prestazioni che consente versatilità e una durata estrema
- Collegamento semplice grazie ai connettori premontati
- Design straordinario e materiali di alta qualità
- Connessione senza utensili con CONNECTsystem opzionale
- Facile installazione su molte superfici lisce grazie al nastro autoadesivo sul lato posteriore

Aree applicative

- Illuminazione di gole
- Integrazione in pareti
- Corrimano e corridoi
- Illuminazione di macchinari
- Illuminazione di sentieri
- Insegne luminose
- Adatti per esterni

Scheda della famiglia di prodotto

Apparecchiatura / Accessori

- Connessione più semplice con il sistema opzionale CONNECTsystem
 - Rapida installazione con il sistema opzionale SLIM TRACK System
 - Abbinamento ideale con gli alimentatori elettronici OPTOTRONIC 24 V
-

Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

Testo delle specifiche

- not relevant
 - not relevant
 - not relevant
 - Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.
-

Supporto tecnico e di vendita

Supporto tecnico e di vendita www.osram.it

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Scheda della famiglia di prodotto

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.