Product family datasheet



# LEDriving PX-5

LED daytime running light for retrofit





LED pixel technology Dynamic appearance thanks to faceted optic and dotted pixel technology



LED daytime running light compatible with a wide range of car models and easy to install



5200 K For drivers who want to increase visibility during the day



#### Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energyefficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

## Product family datasheet

#### Technical data

	General Product Information	Electrical Data		Photometric Data
Product description	Global order reference	Nominal voltage	Nominal wattage	Color temperature
LEDriving PX-5	LEDDRL301	12 V	12 W	5200 K
LEDriving PX-5	LEDDRL301	12 V	12 W	5200 K

		Physical Attributes & Dimensions	Lifetime Data	Additional product data
Product description	Nominal luminous flux	Length	Guarantee	Connector to lamp
LEDriving PX-5	300 lm	160.0 mm	3 years	Wire Kit
LEDriving PX-5	550 lm	160.0 mm	3 years	Wire Kit

	Capabilities	Certificates & standards		Logistical data
Product description	Technology	Approval marks – approval	Standards	Commodity code
LEDriving PX-5	LED	E4 approval	ECE R87	85122000900
LEDriving PX-5	LED	E4 approval	ECE R87	85122000900

		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database		
LEDriving PX-5	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	24fd4b7d-c774-46f3- 9b44-7c1767b813ea		
LEDriving PX-5	Leəd	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7a05b6d4-2aed- 41c9-afdf- 7da8dfd39471		

### Product family datasheet

#### Download Data

	File
	User instruction LED Daytime Running Light Kit LEDDRL301 (User Manual)
7	User instruction LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual)
7	User instruction GPRS_Safety symbols instructions

#### Legal advice

ECE E4 approvalECE R87 approval

#### **References / Links**

Guarantee terms are available at www.osram.com/am-guarantee

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

















