

BackLED M Plus G15

Moduli LED per insegne luminose e retroilluminazione



Caratteristiche prodotto

- Collegato con cavi flessibili
- Classe di protezione (moduli): IP66
- Indice di resa cromatica R_a : > 80
- Omologato CE e UL

Vantaggi prodotto

- Illuminazione uniforme anche con valori di pitch elevati grazie alla tecnologia Square Lens
- Moduli compatibili con il profilato di montaggio per BackLED
- Efficienza dell'applicazione notevolmente migliore rispetto ai sistemi senza lenti
- Diverse opzioni per un montaggio rapido e facile: bulloni o inserimento a scatto
- Eccellente efficienza del modulo
- Durata molto lunga
- 5 anni di garanzia

Aree applicative

- Insegne luminose e illuminazione pubblicitaria
- Retroilluminazione di lettere scatolate di dimensioni medie
- Uso permanente in esterni in scatole luci chiuse o lettere scatolate

Scheda della famiglia di prodotto

Apparecchiatura / Accessori

- Profilo di montaggio BA-SM-MP per BackLED
- Diversi tipi di alimentatori OPTOTRONIC 12 V disponibili

Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

Supporto tecnico e di vendita

Supporto tecnico e di vendita www.osram.it

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Referenze/links

For more information on the multi-level guarantee and the terms and conditions of the guarantee visit [https://](https://www.inventronics-light.com/multilevel-guarantees)

- ▶ www.inventronics-light.com/multilevel-guarantees

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.