

LEDiving BASIC P21/5W



Product family datasheet

Technical data

	Product information		General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDriving BASIC \triangleq P21/5W	Mainly used for signal/ indicator applications	Off-road \triangleq P21/5W	1357CW	1.44 W	12 V

				Photometric Data	Physical Attributes & Dimensions
Product description	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux	Lamp base
LEDriving BASIC \triangleq P21/5W	1 W	$\pm 20\%$	13.5 V	85/25 lm	BAY15d

				Lifetime Data	
Product description	Length	Diameter	Diameter	Lifespan B3	Lifespan Tc
LEDriving BASIC \triangleq P21/5W	38.2 mm	20.0 mm	20.0 mm	2000 hr	2000 hr

	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDriving BASIC \triangleq P21/5W	LED	4052899463295 4052899414518 4052899414495	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC \triangleq P21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9bf3b981-7442-439c-a86d-e513fc794734 fe6d71fd-c80e-400d-8cc2-14ed29394294 1d480114-7d33-4144-80cc-0d5f7210d25e

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

