

OPTOTRONIC Intelligent – DEXAL (SELV)

Linear constant current LED driver – Dimmable



Aree applicative

- Adatto per apparecchi di illuminazione con classe di protezione I

Vantaggi prodotto

- D4i certified SELV DX LED driver up to 80 W due to flexible output characteristic
- Following DiiA Specification Parts -250, -251, -252 and -253
- Wide operating range up to 2100 mA

Caratteristiche prodotto

- Frequenza di linea: 0 Hz | 50 Hz | 60 Hz
- Tensione di alimentazione: 220...240 V
- Monitoraggio dei parametri di esercizio dell'apparecchio

Scheda della famiglia di prodotto

Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

Testo delle specifiche

- The DEXAL interface is polarity sensitive, even if the DEXAL bus power supply in the driver is turned off. Therefore the polarity of all connected drivers should not be mixed.
 - For efficiency and standby power measurement, the D4i bus power supply shall be switched off by using Tuner4TRONIC. Refer to www.tuner4tronic.com.
-

Supporto tecnico e di vendita

Supporto tecnico e di vendita www.osram.it

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.
