HMI DIGITAL 6000 W

HMI DIGITAL | Lampade ad alogenuri metallici, attacco singolo

Aree applicative

- Studio
- Stage
- TV

Vantaggi prodotto

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Caratteristiche prodotto

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Capacità di riaccensione a caldo

© 2024, OSRAM GmbH. Tutti i diritti riservati

Scheda prodotto

Dati tecnici

Dati elettrici

Potenza nominale	600000 W
Tensione nominale	123 V
Corrente nominale	55 A

Dati fotometrici

Flusso luminoso nominale	600000 lm
Temperatura di colore	6000 K
Indice di resa cromatica Ra	90

Dimensioni e peso

Diametro	7500 mm
Lunghezza	3600 mm

Durata

Durata	500 h

Dati di prodotto aggiuntivi

Attacco (denominazione da norma)	GX38

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172005890
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	7c5a8266-8f2a-43a1-95b8-5931d68b0df1

© 2024, OSRAM GmbH. Tutti i diritti riservati

Scheda prodotto

Informazione sulla sicurezza

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Dati logistici

Codice prodotto	Descrizione del prodotto	Unità di imballo (Pezzi/unità)	Dimensioni (lunghezza x profondità x altezza)	Volume	Peso lordo
4062172005890	HMI DIGITAL 6000 W	Cartone di spedizione 1	715 mm x 240 mm x 240 mm	41.18 dm^3	2211.00 g

1)codice prodotto indicato descrive la minore quantità che può essere ordinata. Una unità di spedizione può contenere uno o più di un singolo prodotto. Quando si inserisce un ordine, per la quantità inserire una o più unità di spedizione.

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.

© 2024, OSRAM GmbH. Tutti i diritti riservati