

PL-LIN-Z5 5500-830 1400X20-HV

PrevaLED Linear G5 | Light Engine lineari



Caratteristiche prodotto

- Efficienza modulo: fino a 193 lm/W
- Available with luminous flux: 275 lm on 70 mm
- Temperature di colore disponibili: 3.000 K, 4.000 K o 6.500 K

Vantaggi prodotto

- High voltage (HV) for serial connection
- Low voltage (LV) for parallel connection
- High voltage (HV) optimized for non-isolated, low voltage (LV) optimized for SELV operation

Aree applicative

- Office
- Industria



Dati tecnici

Dati elettrici

Tensione nominale	118 V
Corrente nominale	025 A
Tipo di corrente	DC
On-mode power [AGGR]	30.50 W
Energy consumption in on-mode [AGGR]	30.5 kWh/1000h

Dati fotometrici

Efficienza luminosa	184 lm/W
Indice di resa cromatica Ra	80
Correlated color temperature CCT [AGGR]	3000 K
Colour consistency (McAdam ellipses) [AGGR]	3
Useful luminous flux (Φuse) [AGGR]	4990 lm

Dati illuminotecnici

Tempo innesco	< 01 s
Tempo di riscaldamento (60 %)	< 200 s

Informazioni sul modulo LED

Numero di LED per modulo	180
--------------------------	-----

Dimensioni e peso



Peso prodotto	9400 g
Height EPREL [AGGR]	5.0 mm
Length EPREL [AGGR]	1400.0 mm
Width EPREL [AGGR]	20.0 mm

Temperature e condizioni di utilizzo

Performance temp. acc. to IEC 62717	50 °C
Temperatura di funzionamento	-20...75 °C
Temperatura massima nel punto di prova T	75 °C
Temperatura di stoccaggio	-30...85 °C
Temperatura ambiente	-20...+75 °C

Durata

Numero cicli accensione / spegnimento	100000
Lumen maintenance factor LMF [AGGR]	96
L70B50 lifetime [AGGR]	100000 h

Dati di prodotto aggiuntivi

Lighting technology used [AGGR]	LED
---------------------------------	-----

Certificati, Norme, Direttive

Norme	CE/ENEC/VDE
Grado di protezione	IP20
Energy efficiency class [AGGR]	D

Dati logistici

Codice prodotto di base	85414100000
-------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4052899607323
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained


Scheda prodotto



PL-LIN-Z5 5500-830 1400X20-HV



PL-LIN-Z5 5500-830 1400X20-HV



PL LIN G5 G6 Mounting Guidance 251021

Testo delle specifiche

- When parallel wiring, tolerance-related differences in output are possible and may cause deviations in brightness.

Download dati

File	
	User instruction PrevaLED Linear G5 G6
	Certificati PL ENEC 40031612 250723
	Dichiarazioni di conformità PL LIN Z5 CE 3812250 160623
	Dati CAD 3-dim PL LIN Z5 5500 1400x20 HV CADPDF 240220

Scheda prodotto

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dati logistici

Codice prodotto	Descrizione del prodotto	Unità di imballo (Pezzi/unità)	Dimensioni (lunghezza x profondità x altezza)	Volume	Peso lordo
4052899607323	PL-LIN-Z5 5500-830 1400X20-HV	Cartone di spedizione 60	1427 mm x 295 mm x 120 mm	50.52 dm ³	7016.00 g

1)☒ codice prodotto indicato descrive la minore quantità che può essere ordinata. Una unità di spedizione può contenere uno o più di un singolo prodotto. Quando si inserisce un ordine, per la quantità inserire una o più unità di spedizione.

Clausola

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.