

ICUTRONIC Intelligent – DALI (non-isolated)

Linear constant current LED driver – Dimmable



Aree applicative

- Industry lighting
- Adatto per apparecchi di illuminazione con classe di protezione I

Vantaggi prodotto

- Versatile non-isolated DALI driver up to 75 W due to flexible output characteristic
- Flexible current setting (RSet)
- High-quality dimming of 10...100 % by amplitude dimming
- No TouchDIM nor Corridor Function
- High quality of light thanks to <4% output ripple current
- Low standby power consumption: < 0.25 W

Caratteristiche prodotto

- Frequenza di linea: 0 Hz | 50 Hz | 60 Hz
- Tensione di alimentazione: 220...240 V

Scheda della famiglia di prodotto

Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

Supporto tecnico e di vendita

Supporto tecnico e di vendita www.osram.it

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.