Product family datasheet

OSRAM

BATTERYcharge 908



Start/Stop compatible Suitable for vehicles with Start/Stop system



Winter mode Protects batteries in cold temperatures



9-stage charging cycle For easy charging of Lead Acid/AGM batteries



Smart battery charger and maintainer with multi-stage charging cycle

The OSRAM BatteryCharger 908 is a 8A smart charger and battery maintainer for 12V and 24V vehicles including most cars, vans and small trucks. Maintains and charges a vehicle's battery through a 7 stage charging cycle at the touch of a button for Lithium batteries, with only a 9-stage cycle of Lead Acid/AGM batteries. Includes a backlit LCD digital display to keep things easy even in low light. A host of safety features including reverse polarity and short-circuit protection, keeps both the user and the vehicle safe. Be sure that the charger is maintaining your car battery as it automatically changes to long-term maintenance mode when the vehicle's battery is full.

Product family datasheet

Technical data

| | Product information | Electrical Data | | |
|---------------------|---|----------------------|----------------------|--------------------------------|
| Product description | Application (Category and Product specific) | Min battery capacity | Max battery capacity | Maintainance Charge (up to) |
| BATTERY charge 908 | Smart battery charger | 70 Ah | 150 Ah | 4.0 A |

| | | Physical Attributes & Dimensions | | |
|---------------------|---------------------|----------------------------------|----------|----------|
| Product description | Charge Rate (Up to) | Height | Width | Length |
| BATTERY charge 908 | 8.0 A | 70.0 mm | 106.0 mm | 185.0 mm |

| | Dimensions & weight | | Certificates & standards | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |
|---------------------|---------------------|---------------------|--------------------------------|--|
| Product description | Power Cable Length | Clamps Cable Length | ECE category | Candidate list substance 1 |
| BATTERY charge 908 | 1.5 m | 1.5 m | | Lead |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|---------------------|---------------------------|---|--|
| BATTERY charge 908 | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 39a90b38-e51d-44ff- 8a96-fe9eea625c68 |

Product family datasheet

Download Data

| | File |
|---|--|
| ★ | User instruction BATTERYcharge |
| 7 | User instruction GPRS_Safety symbols instructions |
| D | Movie application BatteryCharge How to Video (ITA) |
| D | Movie application BatteryCharge How to Video (EN) |
| D | Product movie OSRAM BATTERYcharge OEBCS908 Product Video (EN) |
| D | Product movie OSRAM BATTERYcharge OEBCS908 Product Video (DE) |

Legal advice

*for precise conditions please refer to:

www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.