

LF2000 -G3-824-04 L1

LINEARlight FLEX High Power IP00 | Moduli LED per applicazioni professionali e industriali



Caratteristiche prodotto

- Striscia LED flessibile e tagliabile

Vantaggi prodotto

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Ampia scelta di tonalità di luce
- Facile installazione su molte superfici lisce grazie al nastro autoadesivo sul lato posteriore

Aree applicative

- Illuminazione di gole
- Integrazione a soffitto



Dati tecnici

Dati elettrici

Tensione nominale	24,0 V
Tipo di corrente	DC
Potenza nominale al metro	17,9 W
Potenza di costruzione	80,50 W
Gamma di tensione	23...25 V
Accidental reverse input voltage protection up to	25 V

Dati fotometrici

Tonalità di luce del LED	bianco
Indice di resa cromatica Ra	>80
Flusso luminoso al metro	2000 lm
Efficienza luminosa	112 lm/W
Colore della luce (descrizione)	2400 K
Temperatura di colore	2400 K


Dati illuminotecnici

LED pitch	14.29 mm
Ampiezza fascio luminoso	120 °

Informazioni sul modulo LED

Numero di LED al metro	70
Numero di LED per unità più piccola	7

Dimensioni e peso



Lunghezza	4500,0 mm
Lunghezza unità più piccola	100,0 mm

Scheda prodotto

Lunghezza del cavo	500,0
Peso prodotto	65,00 g
Sezione dei cavi, lato ingresso	0.51 mm ²
Larghezza	8,00 mm
Altezza	1,40 mm

Temperature e condizioni di utilizzo

Performance temp. acc. to IEC 62717	50 °C
Temperatura di funzionamento	-20...90 °C ¹⁾
Temperatura ambiente	-20...+50 °C ²⁾
Temperatura di stoccaggio	-40...80 °C

1) Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.
2) Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Durata

Durata caratteristica della lampada	60000 h
Durata nominale della lampada	60000 h

Dati di prodotto aggiuntivi

EAN sostitutivo	4052899952997
ID of contained light source [AGGR]	LS_TRV_217014

Caratteristiche

Lowest bending radius	20 mm
-----------------------	-------

Certificati, Norme, Direttive

Norme	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
Grado di protezione	IP00
Energy efficiency class of the contained light source	F

Dati logistici

Codice prodotto di base	85395100000
-------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172142816

Scheda prodotto

Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	a83efe7b-ba1c-4913-b23c-c13922576da7

Apparecchiatura / Accessori

- Connessione più semplice con il sistema opzionale CONNECTsystem
- Rapida installazione con il sistema opzionale SLIM TRACK System
- Abbinamento ideale con gli alimentatori elettronici OPTOTRONIC 24 V

Testo delle specifiche

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Download dati

File	
	User instruction LINEARlight FLEX POWER
	Product Datasheet LINEARlight Flex Power Specification Sheet
	Brochure Light is freedom of design (EN)
	Certificati VDE ENEC CERTIFICATE 40052516 160823
	Certificati EAC Certificate
	Certificati UL Certificate
	Certificati ENEC10_VDE Certificate
	Certificati CB TEST CERTIFICATE DE1-57844
	Dichiarazioni di conformità LF HP G3 CE 4160937 280623
	Dichiarazioni di conformità LF HP G3 CE 3420012 03 071119
	Dichiarazioni di conformità EU Declaration of conformity

Scheda prodotto

	Dichiarazioni di conformità Manufacturer declaration
	Eulumdat LF2000-G3-824-04 L1 LDT 28032022
	IES data LF2000-G3-824-04 L1 IES 28032022

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dati logistici

Codice prodotto	Descrizione del prodotto	Unità di imballo (Pezzi/unità)	Dimensioni (lunghezza x profondità x altezza)	Volume	Peso lordo
4062172142816	LF2000 -G3-824-04 L1	Cartone di spedizione 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1453.00 g

1)  codice prodotto indicato descrive la minore quantità che può essere ordinata. Una unità di spedizione può contenere uno o più di un singolo prodotto. Quando si inserisce un ordine, per la quantità inserire una o più unità di spedizione.

Accessori opzionali

Descrizione del prodotto	Nome dell'accessorio	Codice dell'accessorio
LF2000 -G3-824-04 L1	CONN-FLEX -2P-050 KIT 10PCS	 4062172179591
LF2000 -G3-824-04 L1	CONN-FLEX -2P-200 KIT 10PCS	 4062172179614
LF2000 -G3-824-04 L1	CORNER-FLEX -4P-003 KIT 10PCS	 4062172179638

Scheda prodotto

LF2000 -G3-824-04 L1	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF2000 -G3-824-04 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF2000 -G3-824-04 L1	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF2000 -G3-824-04 L1	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF2000 -G3-824-04 L1	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF2000 -G3-824-04 L1	FX -SC08-G2-CT4PJ	▶ 4052899464858

Clausola

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.