

TYREinflate 2000



Powerbank-Function

Can be used to charge different electronic devices such as cell phones etc.



LED-Light

High quality LED light for the display as well as for the flashlight function.



Digital & Auto Stop

Digital backlit display and Auto Stop function when pre-set pressure is reached.



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products.

Compact rechargeable tyre inflator



The OSRAM TYREinflate 2000 is a rechargeable tire pump with digital backlit display for easier and more accurate pressure measurements and inflation of tires that displays pressure values in BAR, kPA and PSI. The OSRAM TYREinflate 2000 has an internal memory and thanks to the memory function up to four different values for different tires can be programmed and stored. It is also equipped with an auto-stop function: the OSRAM TYREinflate 2000 stops automatically when the correct and preset pressure is reached. Through the included USB cable, the OSRAM TYREinflate 2000 is rechargeable, and no 12V outlet is required for power supply, so this is not only for inflating car tires, but can also be used for inflating bicycle, scooter and motorcycle tires. The lightweight and compact design of the

OSRAM TYREinflate 2000 makes it ideal for on-the-go use and can be taken almost anywhere. With the included storage bag, simply store in the glove compartment of the car, a bag or rucksack. A bracket for mounting and storage on a bicycle is included. Thanks to the powerbank-function, the OSRAM TYREinflate 2000 can also be used as a charger for electronic devices such as e.g. a mobile phone. In addition, the integrated flashlight function can provide illumination at night or in poor lighting conditions. Also included is a 2-piece adapter set that can be used as a connector for bikes, balls and other inflatables with Presta valves.

OSRAM offers a 2-year guarantee* on this product.




* for precise conditions please refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

Product description	General Product Information	Electrical Data	Physical Attributes & Dimensions	
	Global order reference	Nominal voltage	Length	Width
TYRE inflate 2000	OTIR2000	3.7 V	70.0 mm	70.0 mm
Product description	Height	Operating Conditions	Additional product data	Capabilities
		Noise Level (dB)	Display Type	Fuse
TYRE inflate 2000	170 mm	83 dB	Digital	18 A
Product description	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
TYRE inflate 2000	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	674be9b0-45aa-4d89-9050-1de10cf19353

Download Data

File	
	User instruction TYREinflate 2000
	Movie application TYREinflate OTIR2000 How to Video (DE)
	Movie application TYREinflate OTIR2000 How to Video (EN)

Safety advice

The product may reach a noise level of up to 83 dB

Legal advice

CE and EAC compliant

RoHS 2 201/65/EU and RoHS 3 2015/863

REACH Declaration of Conformity

MSDS (for rechargeable batteries)

* for precise conditions please refer to: www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet and user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.