

## ELEMENT EM FIT Non SELV

Linear / Area a corrente costante – Non dimmerabile



### Aree applicative

- Illuminazione di negozi
- Industry lighting

### Vantaggi prodotto

- Dimensioni ridotte dell'involucro
- High efficiency and reliability
- High light quality due to low ripple current
- Long lasting and high reliability

### Caratteristiche prodotto

- Frequenza di linea: 50 Hz | 60 Hz
- Tensione di alimentazione: 220...240 V
- Wide output voltage range
- Fixed output (no dimming)

## Scheda della famiglia di prodotto

---

### Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

---

### Supporto tecnico e di vendita

Supporto tecnico e di vendita [www.osram.it](http://www.osram.it)

---

### Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.