

LR-P-2000 -927-120D-BK-06-IG-G1 L1

LINEARlight Rigid FINESSE InGround



Caratteristiche prodotto

- Slim, modular LED fixture for linear applications, fully customizable
- Several optics, Wall Grazing and WallWashing; 10°, 30°, 60°
- Outdoor IP67
- Luminous flux: > 2000 lm/m; 1200 m/m; 900 lm/m
- Color uniformity ≤ 2 SDCM
- Lifetime up to 60.000 h L80B10
- Large selection of lighting color temperatures

Vantaggi prodotto

- 3 lengths available to adapt to different conditions
- External metal case available
- Easy to configure the desired light performance for optimal illumination
- Protected against the atmospheric agents: from the desert to the glacier
- Long-time functionality and maintenance-free
- High color fidelity to beautify every design
- Fully controllable by most used light control protocols: DALI, DMX
- Color consistent with LINEARlight FLEX products

Aree applicative

- Wall washing
- Wall Grazing
- Architectural integration



Dati tecnici

Dati elettrici

Tipo di corrente	DC
Accidental reverse input voltage protection up to	25 V
Gamma di tensione	23...25 V

Dati fotometrici

Efficienza luminosa	43 lm/W
Temperatura di colore	2700 K
Tonalità di luce del LED	bianco

Dati illuminotecnici

LED pitch	14.29 mm
-----------	----------

Informazioni sul modulo LED

Numero di LED per modulo	42
Numero di LED per unità più piccola	42

Dimensioni e peso



Peso prodotto	2350,00 g
Lunghezza	676,0 mm
Larghezza	61,5 mm
Altezza	62,0 mm
Lunghezza del cavo	250,0

Temperature e condizioni di utilizzo

Temperatura di stoccaggio	-20...85 °C
---------------------------	-------------

Scheda prodotto

Durata

Related Lifetime L80B10	60000 h
Related Lifetime L90B10	60000 h

Caratteristiche

With end piece	No
With connection set	No
Self-adhesive	No

Certificati, Norme, Direttive

Norme	CE/ENEC
-------	---------

Dati logistici

Codice prodotto di base	94051190900
-------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	02-12-2022
Primary Article Identifier	4062172325646
Declaration No. in SCIP database	In work

Download dati

File	
	User instruction LINEARlight Rigid FINESSE In Ground
	Product Datasheet LINEARlight RIGID FINESSE InGround Specification Sheet
	Brochure Light is awesome - LINEARlight Rigid FINESSE (EN)

Scheda prodotto

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dati logistici

Codice prodotto	Descrizione del prodotto	Unità di imballo (Pezzi/unità)	Dimensioni (lunghezza x profondità x altezza)	Volume	Peso lordo
4062172325646	LR-P-2000 -927-120D-BK-06-IG-G1 L1	Cartone di spedizione 1	780 mm x 180 mm x 140 mm	19.66 dm ³	2920.00 g

1)☒ codice prodotto indicato descrive la minore quantità che può essere ordinata. Una unità di spedizione può contenere uno o più di un singolo prodotto. Quando si inserisce un ordine, per la quantità inserire una o più unità di spedizione.

Clausola

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.