

ICUTRONIC DIM (non-isolated) Sensor KIT

Linear / Area a corrente costante – Dimmerabile



Aree applicative

- Industrial, retail and parking garage lighting

Vantaggi prodotto

- KIT including driver, HF Sensor and cabling
- Non isolated system for energy saving applications
- High quality light with very low ripple
- Enable slim fixture design with flat 21 mm height metal housing
- Long lasting and high reliability

Caratteristiche prodotto

- Flexible with 1 driver offers 4 output currents
- Low THD <10% @ full load
- Input voltage: 220 – 240 VAC
- Ambient temp range ta: -25 to +50 °C
- Low LF-ripple < 5%
- 5 years guarantee*
- HF LI Sensor (Light- and motion detection via radar)
- StepDIM function for different light levels
- Different operating modes for daylight- or motion-dependent switching selectable
- Intervallo di rilevamento del movimento regolabile
- Detection height up to 6 meter

Scheda della famiglia di prodotto

Consigli di applicazione

Per informazioni più dettagliate e grafici consultare la scheda tecnica

Supporto tecnico e di vendita

Supporto tecnico e di vendita www.osram.it

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Clausola

Con riserva di modifiche senza preavviso. Salvo errori o omissioni. Assicurarsi sempre di utilizzare la versione più recente.