

LEDinspect DUAL CHARGE PAD



Wire-Free Technology

Simply place a compatible worklight on the charging pad to easily hold and recharge



Flexible mounting options

With strong magnets and screw holes built-in, you can easily attach the charging pad to toolboxes, workbenches and more



Built to last

IK08 and IP20 rated to survive the rigors of the professional workshop



The easiest way to recharge two inspection lamps

Removing the need to find and connect the correct charging cable, OSRAM's Wire-Free charging pad securely stores and recharges a pair of suitable inspection lamps, so they are ready when you are. This innovative design not only enhances convenience but also supports an uninterrupted workflow.

Product family datasheet

Technical data

	Product information	General Product Information	Physical Attributes & Dimensions			
Product description	Application (Category and Product specific)	Global order reference	Height		Width	
CHARGING PAD	LED inspection lights	LEDIL424	105 mm	105 mm 106.0 mm		
			Lifetime Data	Capabili	ities	
Product description	Length	Product weight	Guarantee	Technol	logy	
CHARGING PAD	202.2 mm	220.00 g	2 years	LED		
	Environmental & Regulation Information according	ulatory Information Art. 33 of EU Regulation	(EC) 1907/200	6 (REACh))	
Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction		Declaration no. in SCIP database	
CHARGING PAD	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the		298f9330-2cce-45e2- 84a3-cadbe07428a5	

article.

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



User instruction

LEDinspect SINGLE CHARGE PAD / DUAL CHARGE PAD

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.